

TUBEFORMER PLUS

The new generation of Spiro® Tubeformer delivers the best duct for your buck!

Perfected by Swiss engineering and with attention to detail, the latest Spiro® Tubeformer innovation increases your return on investment to unprecedented levels.

The modular approach enables you to optionally upgrade the basic machine with a Spiro® heavy duty kit.

Unique Features

- » New flying slitter
- » Designed for quick change over
- » Sophisticated and user-friendly interface
- » Continuous assurance of Spiro® quality seam
- » Captures all common HVAC material thicknesses & sizes



Technical Data

Diameter Range	80 - 1600 mm (3,15" - 62,99")
Strip Thickness	0.4 - 1.25 mm (0.015" - 0.049") galvanized steel 0.4 - 0.6 mm (0.015" - 0.023") stainless steel 0.4 - 1.25 mm (0.015" - 0.049") aluminium
Cutting System Slitter - Smooth and Noiseless Cut	Flying slitter
Basic Machine	Frequency controlled main drive Vertical decoiler & Run-off table Corrugation unit Quick cassette change over system Automatic length measurement system
Performance Tested / Guaranteed (duct of 3 m length)	0.5 mm (0,020") thickness – 100 mm (3,94") diameter – 250 Ducts/hour
	0.7 mm (0,028") thickness – 500 mm (19,69") diameter – 63 Ducts/hour
	0.9 mm (0,035") thickness – 1250 mm (49,21") diameter – 18 Ducts/hour
	1.25 mm (0,049") thickness – 1600 mm (62,99") diameter – 10 Ducts/hour



Individual engraving possible



Fixed lock seam and assured duct quality