

TUBEFORMER X-20

This rigid and highly mobile Tubeformer is ideal for on-site work and performs strongly in a rough environment. The compact design and selected technology allows for an easy relocation to a new worksite.

The spiral duct machine captures the All-In-One approach, including the run-off table, decoiler, automatic discharge function, corrugation unit, Spiro® Flying Slitter and standard tooling up to 1.0 mm.

The Tubeformer X-20 design accomplishes the HVAC-industry requirements to produce in galvanized steel, stainless steel or aluminium, as well as fulfilling the DIN, EUROVENT and SMACNA standards.

Unique Features

- » Compact & Rigid Design
- » Reduced Maintenance
- » High Mobility
- » FRU Cassettes For Quick Set-Up



Registered Design:
2153601-0001/-0002



The new generation of the SPIRO® FLYING SLITTER utilizes extra strong linear guides in combination with the strength of the toggle joint to achieve the perfect cut.

Technical Data

Diameter Range	80 - 1250 mm (3" - 50")
Strip Thickness	0.4 - 1.0 mm (0.016" - 0.039") galvanized steel 0.4 - 0.6 mm (0.016" - 0.024") stainless steel 0.6 - 1.0 mm (0.024" - 0.039") aluminium
Cutting System Slitter - Smooth and Noiseless Cut	Second Generation Spiro® Flying Slitter
Performance Tested / Guaranteed (duct of 3 m length)	0.5 mm (0.020") thickness – 100 mm (4") diameter – 180 Ducts/hour
	0.7 mm (0.028") thickness – 500 mm (20") diameter – 53 Ducts/hour
	0.9 mm (0.035") thickness – 1250 mm (50") diameter – 23 Ducts/hour